Combustible Gas leak detectors

719, 720b, 721, 775



L FCGLD 05.09.axd

Delivering test and measurement advantages for HVAC/R professionals worldwide

Test the TPI advantage

APPLICATIONS

- Detect combustible gases including natural gas methane, propane (LPG), gasoline, diesel, kerosene, etc.
- Trace natural gas lines and fittings for leaks
- Check gas operated equipment for leaks

Pipi 719 Computation One Computation Comp	TICK ADJUST Confluentina Case Lask Delactor 7200	SOUTION TO THE PROPERTY OF THE	Combustinie dies
719	720b	721	775

Test Products International, Inc. Headquarters: 9615 SW Allen Blvd. Beaverton, OR 97005 USA

503-520-9197 Fax: 503-520-1225

email:

info@tpi-

thevalueleader.com

	robuct No.	Detects 50 ppm or greater methane	Detects 30 ppm or greator methane	Detects 10 ppm or greator methane	Alarm light in tip	Display leaks in real ppm, stepped ppm, and %LEL (Lower Explosive Limit).	Measure ambient CO in ppm
	719	√	√		✓		
7	720b	√	√	√			
	721	√	√	√	✓	√	
	775	√					√

TPI 719, 720b, 721 Features

- Quick and simple operation
- Visual and audible leak detection
- Adjustable tic rate
- Optional earphone attachment
- One-hand operation
- •16" gooseneck probe length
- 3-Year Limited Warranty

www.tpithevalueleader.com

Copyright © 2009 Test Products International, Inc.

Accessories

Adapters | Cables & Connectors | Oscilloscope Probes | Test Leads

Clamp-on Meters (Current)

Combustion Efficiency Analyzers (Flue Gas Analyzers)

Food Safety, Processing, & Preperation

Gas Detection

Carbon Monoxide (CO) | Combustibles | Refrigeration Leak Detectors

Indoor Air Quality (IAQ)

Manometers (Pressure)

Multimeters (DMMs)

Oscilloscopes (Handheld)

Specialty Testers

Insulation | Multifunction | Photo-tachometer

Temperature

Contact | Non-contact (IR) | Pocket Digital Thermometers

Temperature Probes

J-Type | K-Type | T-Type |

Thermistor Test Leads & Accessories

Fused | Modular | Screw-on | Push-on

Test Products International, Inc.

Headquarters:
9615 SW Allen Blvd.
Beaverton, OR 97005 USA
503-520-9197
Fax: 503-520-1225
info@tpi-thevalueleader.com

Specifications	ications Products			
/ Feature	719	720b	721	775
Specifications	Leak Detection Sensitivity (methane): 30ppm Visual and audible indication of combustible gas leaks Detect combustible gases including natural gas, propane, butane, etc. Adjustable tic rate via side thumb wheel Alarm Indication: Visual and audible Goose Neck: 16" long with visual alarm indicator in sensor housing	Leak Detection Sensitivity (methane): 10ppm Visual and audible indication of combustible gas leaks Detect combustible gases including natural gas, propane, butane, etc. Thumbwheel adjustable tic rate to locate leaks quickly and accurately Audio / Visual alarm indication with user adjustable alarm point Earphone jack for use in noisy environments	Leak Detection Sensitivity (methane): 10ppm Dual display with analog bargraph and backlight Display Modes: Real (ppm), Leak Level (stepped ppm), %LEL Detect combustible gases including natural gas, propane, butane, etc. Ranges:	Leak Detection Sensitivity (methane): 50ppm Carbon Monoxide: 0 to 2000ppm Display Type: Dual display with backlight Display Modes: Leak Level (stepped ppm), CO (ppm) Measure carbon monoxide and detect combustible gases including natural gas, propane, butane, etc. Audible Leak Indication: Adjustable tic rate via side thumb wheel Alarm Indication: Visual and audible (User adjustable alarm level) Sensor Test and Zero: Automatic at start up Goose Neck: 16" long with visual alarm indicator in sensor housing
Feature	Visual and audible indication of combustible gas leaks. 30ppm sensitivity (methane) Detect combustible gases including natural gas, propane, butane, etc. Thumbwheel adjustable tic rate to locate leaks quickly and accurately. Audio / Visual alarm indication with user adjustable alarm point. Earphone jack for use in noisy environments. Approximately 20 hours of continuous use (C cell alkaline batteries x2)	Visual and audible indication of combustible gas leaks. 30ppm sensitivity (methane) Detect combustible gases including natural gas, propane, butane, etc. Thumbwheel adjustable tic rate to locate leaks quickly and accurately. Audio / Visual alarm indication with user adjustable alarm point. Earphone jack for use in noisy environments. Approximately 20 hours of continuous use (C cell alkaline batteries x2)	Combustible Gas Leak Detector capable of displaying real ppm, stepped ppm, and %LEL (Lower Explosive Limit). 10ppm sensitivity (methane) Detect combustible gases including natural gas, propane, butane, etc. Thumbwheel adjustable tic rate to locate leaks quickly and accurately. Two line display with bargraph and backlight Audio / Visual alarm indication with user adjustable alarm point. Earphone jack for use in noisy environments. Approximately 20 hours of continuous use (C cell alkaline batteries x2)	Combustible Gas Leak Detector capable of measuring carbon monoxide 50ppm sensitivity (methane) 1ppm sensitivity (carbon monoxide) Detect combustible gases including natural gas, propane, butane, etc. Thumbwheel adjustable tic rate to locate leaks quickly and accurately. Two line display with backlight Audio / Visual alarm indication with user adjustable alarm point. Earphone jack for use in noisy environments. Approximately 20 hours of continuous use (C cell alkaline batteries x2)

Products	Standard Accessories		Optional Accessories	
719	Part number A739 A709A A700	Description Combustible gas sensor Sensor cage Soft pouch	Part number A710 A700SG	<u>Description</u> Earphone Soft carrying case
720b	Part number A739 A709A A700	<u>Description</u> Combustible gas sensor Sensor cage Soft pouch	Part number A710 A700SG	<u>Description</u> Earphone Soft carrying case
721	Part number A739 A709A A700	Description Combustible gas sensor Sensor cage Soft pouch	Part number A710 A700SG	<u>Description</u> Earphone Soft carrying case
775	Part number A739 A760 A709A A700	Description Combustible gas sensor Carbon Monoxide Sensor Sensor cage Soft pouch	Part number A710 A700SG	<u>Description</u> Earphone Soft carrying case